

MECHANICAL FEATURES

Device dimensions:	1159 x 500 x h460 mm 45.6 x 19.7 x h18.1 in	Sky-light size:	498 x 295 mm (x2) 19.6 x 11.6 in (x2)
Necessary space for installation (largest volume including device, assembled frame, fixing kit):	1159 x 500 x h460 mm 45.6 x 19.7 x h18.1 in	Weight:	24 Kg 55 lb
Fixing kit:	The fixing kit includes 4 threaded rods (0.5 m; M6 metric system)		

ELECTRICAL FEATURES

Type of source:	LED
Light output control:	Dimmable by DALI
Light output range:	0.1-100%
Power input:	4 channels, 450 mA each channel, 42 Vdc
Max power consumption:	80W
Typical power consumption:	80W
Power supply:	Not included. Suggested power supply: MOONS MU050S150BQI511 (x2)

FRAME

Material:	Powder-coated steel sheet
Visible dimensions:	Depending on the configuration
Weight:	7 kg / 15.4 lb
Finishing:	White

DESCRIPTION

CoeLux® LS Array is a recessed ceiling system that artificially reproduces natural light from the sky and the sun. It includes an LED light source, optical components and a CoeLux® panel, all housed in a plastic structure. Skylight dimensions: (2x)498 x 295 mm | (2x)19.6 x 11.6 in). Appearance of the sun: visible, slightly frosted. Beam direction: 45°. Appearance of the sky: clear. Frame: included (mandatory for optimal yield), matte. It may also be mounted on normally inflammable surfaces. Inspection hatch: not required. For Array configurations use LS Array Head module and LS Array Middle module in variable number.

OPTICAL FEATURES

Total Light Output*:	3000 lm
Lumen maintenance (L90B10)*:	> 50000h
LED CRI (Ra) :	> 92
CCT of transmitted beam:	4800K
CCT of the Sky:	> 30000 K

Photometric diagram (simulated .ies .ldt file, without frame): Available

Beam angle:	45°
Divergence (H/V) (without frames, refer to photometric curves)	13° / 18°
Sun appearance:	Visible slightly frosted
Sky appearance:	Clear
Melanopic Ratio (Sky):	1,577
Melanopic Ratio (Sun):	0,822

OPERATING CONDITIONS

Min/max operating temperature:	-10/40°C
Max operating relative humidity (no condensing):	95%
IP grade:	IP20 (IP44 on the sky panel side only)


SHIPPING INFORMATION

_ No. 3 Carton boxes:
 1200x500x650 mm / 47.2x19.7x25.6 in - 32 kg / 70.5 lb and
 1250x660x185 mm / 49.2x26.0x7.3 in - 10 kg / 22 lb and
 1250x660x185 mm / 49.2x26.0x7.3 in - 10 kg / 22 lb
 Dimensions and weights may differ depending on packaging and shipping conditions.

CERTIFICATIONS

Certifications:	CCC
Certification code:	CoeLux LS (Serie 2)

PHOTOMETRIC CURVES



Profiles (cd)
 — C0 - C180
 — C90 - C270

All values marked with an * are rated values.

CoeLux technical sheets and 3D files can be downloaded directly from our website www.coelux.com

The products here presented are covered by patents and patents applications. Details available at www.coelux.com/en/patents/index

CoeLux reserves the right to carry out variations to technical details.